260

Lifting system with swivel booms

for containers with ISO corners, up to max. **12 t total weight**



With swivel booms, the supports are folded into transport or working position.
For front installation, a distance of at ca. 600 mm is required between the driver's cab and the container.

- Simple installation on the ISO corners
- Installation universally adjustable for either front or longitudinal locking
- Versions for different container dimensions
- Manual operation with hand crank - optionally with a connecting shaft.
- Optionally with electric motors and automatic levelling control (0° or ground parallel)
- Lifting height up to max. 2.000 mm (under reduced conditions)
- Ground inclination up to 7° possible (under reduced conditions)

HETEK Lift- und Hebetechnik GmbH
Unter den Linden 1
D-99830 Treffurt

Tel.: +49 36923 53-0
E-Mail: info@hetek.de
Internet: www.hetek.de

260

Lifting system with swivel booms

for containers with ISO corners, up to max. **12 t total weight**

Model	260-T01
Maximum load capacity in the system	up to 12.000 kg
Maximum load capacity per support	up to 6.000 kg
Lifting height Maximum lifting height (under reduced conditions)	1.750 mm - standard up to 2.000 mm
Allowed ground inclination Maximum ground inclination (under reduced conditions)	3,5° - standard up to 7,0°
Control tolerance for level control	±0,25° absolute
Wind load	20 m/s (72 km/h) - standard
Operating temperature range	-32°C - +49°C - standard
Power connection for electric drive	24 VDC | 400 VAC | 230 VAC









HETEK Lift- und Hebetechnik GmbH
Unter den Linden 1
D-99830 Treffurt

Tel.: +49 36923 53-0
E-Mail: info@hetek.de
Internet: www.hetek.de