260

Lifting system with pull-out booms

for containers with ISO corners, up to max. **12 t total weight**



With the pull-out booms, the supports are slided into the transport or working position.
A distance of at least 250 mm is required between the driver's cab and the container.
Also available as a mixed set (front with pull-out booms, rear with svivel booms)

- Installation on the ISO corners
- Versions for different container dimensions
- Manual operation with hand crank - optionally with a connecting shaft.
- Optionally with electric motors and automatic levelling control (0° or ground parallel)
- Lifting height up to max. 2.000 mm (under reduced conditions)
- Ground inclination up to 7° possible (under reduced conditions)

HETEK Lift- und Hebetechnik GmbH
Unter den Linden 1
D-99830 Treffurt

Tel.: +49 36923 53-0
E-Mail: info@hetek.de
Internet: www.hetek.de

260

Lifting system with pull-out booms

for containers with ISO corners, up to max. **12 t total weight**

Model	260-T02
Maximum load capacity in the system	up to 12.000 kg
Maximum load capacity per support	up to 6.000 kg
Lifting height	1.750 mm - standard
Maximum lifting height (under reduced conditions)	up to 2.000 mm
Allowed ground inclination	3,5° - standard
Control tolerance for level control	±0,25° absolute
Wind load	20 m/s (72 km/h) - standard
Operating temperature range	-32°C - +49°C - standard
Power connection for electric drive	24 VDC | 400 VAC | 230 VAC







HETEK Lift- und Hebetechnik GmbH
Unter den Linden 1
D-99830 Treffurt

Tel.: +49 36923 53-0
E-Mail: info@hetek.de
Internet: www.hetek.de